

Important instructions regarding the internal connector

When using the internal Firewire connector (PORT01), don't plug any device to the first external port (PORT0).

Software installation

Installation under Windows XP:

The Firewire card gets installed automatically. You can check if Windows has installed the interface card properly.

Click ⇒ Start ⇒ Control Panel (in the classic start menu ⇒ Start ⇒ Settings ⇒ Control Panel) ⇒ Printers and Other Hardware and then on System below "See Also" (In the classic view please double click on System). In the window system properties please continue with ⇒ Hardware ⇒ Device Manager. In the section IEEE 1394 Bus host controllers must be an entry "VIA OHCI Compliant IEEE 1394 Host Controller" without a yellow exclamation mark.

Installation under Windows ME:

The card gets installed automatically. Answer the following question about the restart with ⇒ **Yes**.

You can check if the IEEE 1394 card has been installed properly. Click ⇒ **Start** ⇒ **Settings** ⇒ **Control Panel** ⇒ **System** ⇒ **Device Manager** ⇒ **1394 Bus Controller**. There must be an entry "VIA OHCI Compliant IEEE 1394 Host Controller" without a yellow exclamation mark.

Installation under Windows 98 SE:

Shortly after booting, the system is starting the **Add New Hardware Wizard** and searches for new drivers for "PCI OHCI Compliant IEEE 1394 Host Controller". Please click on ⇒ **Next**. In the following window ("What do you want Windows to do?") select "**Search for the best driver for your device**" ⇒ **Next** ⇒ **Next** ⇒ **Next**. Windows is now copying the necessary drivers. Insert the **Windows 98 CD-ROM** if needed and then click on "**OK**" (Possibly you must then enter another drive letter for your CD-ROM drive). Afterwards please click on ⇒ **Finish**. You can check if the IEEE 1394 card has been installed properly. Click ⇒ **Start** ⇒ **Settings** ⇒ **Control Panel** ⇒ **System** ⇒ **Device Manager** ⇒ **1394 Bus Controller**. There must be an entry "PCI OHCI Compliant IEEE 1394 Host Controller" without a yellow exclamation mark.

Installation under Windows 2000 Prof.

The Firewire card gets installed automatically. You can check if Windows has installed the interface card properly. Click ⇒ **Start** ⇒ **Settings** ⇒ **Control Panel** ⇒ **System** ⇒ **Hardware** ⇒ **Device Manager** ⇒ **IEEE 1394 Bus host controllers**. There must be an entry "VIA OHCI Compliant IEEE 1394 Host Controller" without a yellow exclamation mark.